

## FT-930R 4 Channels active Analog and **AHD/HDCVI / TVI** video receiver



### ◎ Features

4CH Active Analog and **AHD/HDCVI / TVI** UTP Receiver. This device is capable of receiving and transmitting videos signal over UTP cable.

### ◎ Tech Info.

Model	FT-930R
Specification	4CH Active
Video out	4CH BNC(female)
Audio/data	NO
Power	12V AC/DC
Impedance	Coax, male BNC:75Ω UTP (Screwless) Terminal Block or UTP RJ45 Data Connector:100Ω
Transmission distance	AHD/HDCVI/TVI:passive to active receiver, 720P/960P Camera:AHD800m, TVI/CVI 600m, 1080P Camera:AHD 600m, TVI/CVI 400m
Wire type	One Unshielded Twisted Pair 24-16AWG(0.5-1.31mm) Per video signal: DC Loop Resistance 52 ohms per 1,000 ft(18 ohms per 100m)
Surge suppression	6000V 10Us*700uS IEC61000-4-5
Video format	NTSC / PAL /CCIR /SECAM analog real-time signal
Frequency range	DC 6MHz;Common mode rejection:60db
Control	Brightness and Sharpness
UTP Port	RJ45 and 8Pin connector
Dimensions (mm)	120*82*32
Weight (g)	200
Environment	Temperature:-10~+50℃ Humidity:0~95%